



Philips
Scart cable

1.5 m

Component Video/Stereo Audio

SWV6662



Enjoy the ultimate viewing experience

Take your components to optimum performance. This top-of-the-line cable offers the best connection for transferring audio/video signals between components.

Enjoy better picture quality

- 24 carat gold-plated connectors optimise signal
- 4-Cut connectors for secure connections
- Split centre pin for better signal transfer
- 99.97% Oxygen-Free Copper (OFC)

Protects against signal loss

- 100% aluminium shielding
- Oxygen-free copper conductor for ideal signal transfer
- Copper-braided reinforced aluminium shielding

Easy installation

- Colour-coded connectors for instant recognition
- Plug and play for easy use

Enjoy extended durability

- Heavy-duty brass shell for extended durability
- Super pliable jackets for outstanding flexibility

PHILIPS
sense and simplicity

Specifications

Inner Box

- EAN/UPC/GTIN: 87 12581 31460 6
- Quantity: 2
- Gross weight: 1.54 kg
- Tare weight: 0.28 kg
- Net weight: 1.26 kg
- Length (cm): 35 cm
- Width (cm): 24.5 cm
- Height (cm): 27.5 cm

Outer Box

- EAN/UPC/GTIN: 87 12581 31461 3
- Quantity: 4
- Gross weight: 4 kg
- Tare weight: 0.94 kg

- Net weight: 3.06 kg
- Length (cm): 50 cm
- Width (cm): 37 cm
- Height (cm): 29 cm

Packaging

- EAN/UPC/GTIN: 87 12581 31459 0
- Quantity: 1
- Gross weight: 0.62 kg
- Tare weight: 0.1 kg
- Net weight: 0.52 kg
- Height: 12 cm
- Length: 33 cm
- Width: 25 cm

Highlights

Colour-coded connectors

Colour-coded connections make it easy to install your cable into the correct inputs and outputs

4-Cut connectors

4-Cut connectors ensure secure connections between your component and your cable.

Split centre pin

The split centre pin allows for better signal transfer and an improved connection to the component inputs.

99.97% OFC solid conductor

99.97% Oxygen-free copper (OFC) cable core provides optimum signal quality.

100% aluminium shielding

This protective layer of aluminium guards against electromagnetic interference for improved signal quality.

Twisted high-purity OFC

This oxygen-free copper conductor provides the highest accuracy in signal transfer with minimal resistance.

Braided shielding

Copper-braided reinforced aluminium shielding protects against signal loss and interference.

Heavy-duty brass shell

The heavy-duty brass shell protects the internal connection of the cable. It ensures durability and the reliability of your connection.

Super pliable jackets

Super pliable PVC jackets are abrasion-resistant for outstanding flexibility and protection against everyday wear and tear.

Plug and play

Plug and play offers easy installation of components without time-consuming installations.



Issue date 2009-03-09

Version: 1.0.3

12 NC: 8670 000 26831
EAN: 87 12581 31459 0

© 2009 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips
Electronics N.V. or their respective owners.

www.philips.com